# Technical Data Sheet
# SHOOLIN ACF
## Acrylic White Crack Filling Compound

SHOOLIN®

## DESCRIPTION

Shoolin ACF India's first Acrylic Crack Flling Compound is of a professional quality product. Shoolin ACF prevents air and moisture from passing through cracks and joint, offers excellent flexibility to resist expansion and contracting without cracking. paintable with latex and oil based paints. Useful for both interior as well as exterior.

## RECOMENDED USES

- Concrete
- Plaster
- Brick
- Drywall
- Painted surface
- Wood
- Metal

## CHARACTERSTICS

- **Color:** White and Light Grey
- **Consistency:** Smooth and Creamy
- **Odor:** Very Mild
- **Vehicle:** Acrylic Polymer
- **Volatile:** Water
- **Tooling time:** 10 Minutes
- **Track Free Time:** 30 Minutes
- **Temperature Service Range:** -200 C To900c.
- **Temperature Application Range:** 30 C To400 C.
- **Freeze thaw Stability:** Passes 5 Cycles
- **Paintability:** Yes
- **Shelf Life:** 18 Months
- **Max Gap filling Capacity:** Up To 12 Mm

## APPLICATION

- Window and door
- Frames corner
- Joints baseboard
- Moulding
- Vents
- Sliding and trim
- Other gaps & openings

## APPLICATION METHOD

- Remove old caulk from surface.
- Make sure that surface is clean, dry and free of loose debris
- Trim the nozzle to the desired bead size
- Then puncture the foil using any pointed object.
- Load the cartridge into caulking gun.
- Hold the cartridge at a 45 angle and fill the seam with ample amount of sealant.

## PACKING

- Standard packing: 1 kg. tin

## COLOUR

- white or light grey after drying

## SHELF LIFE

- 24 Months

## PRECAUTION

- Do not use in high abrasion area or underwater.

SHOOLIN